


EN **2 Flute End Mills (Slot Drills)**
Milling keyways and slots to size in one cut. Designed for plunging operations.

FR **Fraises 2 goujures (Fraises à Rainurer)**
Pour le fraisage de rainures en une seule passe. Conçue pour les opérations de soyage.

DE **Schaftfräser (Bohrnutenfräser), 2-schneidig**
Maßfräsen von Keilnuten und Kerben in einem Durchgang. Für Eintauchvorgänge ausgelegt.

ES **Fresas de forma de 2 ranuras (brocas para ranurar)**
Fresado de ranuras y chavetas en un solo corte.
Diseñada para operaciones de inmersión.

PY **2-х перые концевые фрезы (шпоночные фрезы)**
Для фрезерования шпоночных пазов и уступов.
Конструкция позволяет осуществлять врезание под углом.


 Code
Código
Код

350

 Properties
Propriétés
Eigenschaften
Propiedades
Свойства

mm	BS 122	HSS Co8e
	TYPE N	
	30°	Z 2
	UNCOATED TiAIN	

d	l ₂	l ₁	d ₁	Code Código Код	
				Uncoated Non-Revêtus Unbeschichtet Sin Revestimiento Без Покрытия	TiAIN Coated Revêtus TiAIN TiAIN-beschichtet Revestimiento de TiAIN Покрытие TiAIN
2	4	51	6	3500200	3500200A
2.5	6.5	54	6	3500250	3500250A
3	11	60.5	6	3500300	3500300A
3.5	12.5	66.5	6	3500350	3500350A
4	12.5	66.5	6	3500400	3500400A
4.5	12.5	66.5	6	3500450	3500450A
5	12.5	70	6	3500500	3500500A
5.5	16	76	6	3500550	3500550A
6	16	76	6	3500600	3500600A
6.5	16	76	10	3500650	3500650A
7	16	76	10	3500700	3500700A
7.5	16	76	10	3500750	3500750A
8	19	79.5	10	3500800	3500800A
8.5	22	82.5	10	3500850	3500850A
9	22	82.5	10	3500900	3500900A
9.5	22	82.5	10	3500950	3500950A
10	22	82.5	10	3501000	3501000A
11	22	89	12	3501100	3501100A
12	25.5	95	12	3501200	3501200A
13	25.5	95	12	3501300	3501300A
14	28.5	101.5	12	3501400	3501400A

d	l ₂	l ₁	d ₁	Code Código Код	
				Uncoated Non-Revêtus Unbeschichtet Sin Revestimiento Без Покрытия	TiAIN Coated Revêtus TiAIN TiAIN-beschichtet Revestimiento de TiAIN Покрытие TiAIN
*15	31.5	108	12	3501500	3501500A
16	31.5	108	16	3501600	3501600A
17	35	114.5	16	3501700	3501700A
18	35	114.5	16	3501800	3501800A
19	38	120.5	16	3501900	3501900A
20	38	120.5	16	3502000	3502000A
22	41.5	140	25	3502200	3502200A
24	41.5	152.5	25	3502400	3502400A
25	44.5	159	25	3502500	3502500A
26	44.5	159	25	3502600	3502600A
28	47.5	159	25	3502800	3502800A
30	51	159	25	3503000	3503000A
32	51	159	32	3503200	3503200A
35	54	159	32	3503500	3503500A
36	54	159	32	3503600	3503600A
38	57	159	32	3503800	3503800A
40	63.5	159	32	3504000	3504000A
42	63.5	159	32	3504200	3504200A
45	63.5	159	32	3504500	3504500A
50	63.5	159	32	3505000	3505000A

* Not to BS 122
Non conformes à BS 122
Nicht nach BS 122
No conforme a BS 122
Размер не по BS 122

Application Anwendung Aplicación Применение	HIGH TENSILE STEELS ACIERS À HAUTE RÉSISTANCE HOCHFESTER STAHL ACERO DE ALTA RESISTENCIA TENSIL ВЫСОКОПРОЧНАЯ СТАЛЬ	GENERAL ALLGEMEINE ОБЩЕЕ
---	--	---



Shank Cutters
Fraises à queue
Schaftfräser
Cortadoras de mango
Хвостовые фрезы